### ANTIFREEZE/COOLANT DATA SHEET



### **Euro 50/50**

252-1520



FORMULATED FOR	OE REFERENCE NUMBER
AUDI/VOLKSWAGEN	ZVW 237 105
BMW/MINI	82 14 1 467 704
MERCEDES-BENZ/SMART	Q 1 03 0004
VOLVO	31439821

ATTRIBUTES	
APPEARANCE	Blue
DENSITY AT 20°C	1.12 g/cm <sup>3</sup>
FLASH POINT	>100°C/>212°F
WATER CONTENT	<3%
PH-VALUE	~7.5 - 9.0
BOILING POINT	107°C /225°F**
FREEZING POINT	-37°C/-35°F

<sup>\*\*</sup>Using a 15 psi (103 kPa) pressure cap at sea level

Beck/Arnley Euro 50/50 is a prediluted premium antifreeze based on monoethylene glycol. Contains no nitrates, amines or phosphates. Euro 50/50 provides superior corrosion and rust protection of water-cooled automobile engine cooling system components.

#### ADVANTAGES AND BENEFITS

- For use in both iron and aluminum engines
- Superior anti-corrosion properties allow longer life
- Protection against foaming and cavitation
- Produced and packaged in Germany

## IN COMPLIANCE WITH THE FOLLOWING SPECIFICATIONS

- ASTM D3306/D4985
- AFNOR NF R 15-601
- BS 6580
- SAE J1034
- BMW N60069.0
- Deutz
- MAN 324 NF/Pritader
- MB 325.00
- MINI N60069.0
- MTU MTL 5048
- OPEL/GM B 040 0240
- VW TL 774-C (G11)

Our 50/50 prediluted formulations are ready to use. We use deionized water for purity. The deionization process removes the impurities and minerals from the water which may make the antifreeze/coolant less effective over time.

# PREDILUTED FORMULATIONS ARE READY TO USE. DO NOT ADD WATER.

Always check owner's manual for proper application.

UNIT SIZE	PART NUMBER
1.057 GAL. (4.0 LITERS)	252-1520



Braking | Engine: Electrical | Engine: Mechanical | Fluids | Steering/Suspension/Driveline

